(19) World Intellectual Property Organization

International Bureau



T BORRA BURRAR I II BORRA BIRAN BORRA BORRA BURRA BIR I DA BURBAR BURRA BURRA BURRA BURRA BIRAN BORRA BURRA BURRA BURRA

(43) International Publication Date 23 June 2005 (23.06.2005)

PCT

(10) International Publication Number WO 2005/056459 A1

(51) International Patent Classification7:

B66B 11/04

(21) International Application Number:

PCT/KR2004/001576

(22) International Filing Date:

29 June 2004 (29.06.2004)

(25) Filing Language:

Korean

(26) Publication Language:

English

(30) Priority Data: 20-2003-0038537


10 December 2003 (10.12.2003) KR

- (71) Applicants and
- (72) Inventors: HUR, Jae-Young [KR/KR]; 104-1405 Han Kook A.P.T., #643-2, Bugae-dong, Bupyeong-gu, Incheon 403-721 (KR). BAEK, Rak-Chun [KR/KR]; #A-603, Samsungchereville A.P.T., Sinjeong 6(yuk)-dong, Yangcheon-gu, Seoul 158-762 (KR).

- (74) Agents: SONG, Jae-Ryun et al.; 5th fl., Nongshim bldg., #209, Seogye-dong, Yongsan-gu, Seoul 140-710 (KR).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: ELEVATOR TRACTION MACHINE



(57) Abstract: The present invention relates to an elevator traction machine, and more particularly, to an elevator traction machine, wherein a plurality of planetary gears are coupled to be circumscribed and engaged with a sun gear formed at one end of a driven shaft in order to reduce high speed rotation transmitted from a driving motor and to wind wires on a sheave, and pinions formed at the other sides of the planetary gears are circumscribed and engaged with a plurality of other planetary gears or a fixed sun gear so that planetary gears just before the fixed sun gear can be rotated together with a flange, thereby obtaining reduction effects for a gear ratio among the sun gears, pinions and planetary gears, and noise/vibration-reducing effects and large rotational force-transmitting effects due to formation of the gears out of helical gears.

WO 2005/056459 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

with international search report